

DRUMNET® Tight Head Drum

The drum reduces residues of liquids substances. In an upside-down position the product flow is directed into the open 2" bung without additional manipulations.

The Tight Head drum is compatible with all current industry facilities. The international standard steel drum for lub-oil, chemical, pharmaceutical and food stuff industries.



Features

- "W" Hoop available for maximum freight utilization and superior vacuum resistance.
- Available with multiple closure and fitting designs.
- Leak testing available for quality assurance.
- Triple seam construction to ensure integrity and durability.
- Versions available to meet UN performance standards for reuse.
- Approved linings to comply with international regulations.

Technical Data.....

Capacity	Thickness			W Hoop with corrugations		W Hoop	
	Top	Body	Bott.	Height	Weight	Height	Weight
210L	0,80	0,80	0,80	880±3	14,3±0,7	880±3	14,3±0,7
	1,00	0,80	1,00	880±3	14,9±0,7		
	1,00	0,90	1,00	880±3	16,2±0,7	880±3	16,2±0,7
	1,00	1,00	1,00			880±3	17,8±0,8
	1,20	1,10	1,20	880±3	19,5±0,8	880±3	19,5±0,8
	1,50	1,20	1,50	880±3	22,4±0,8		
225L	0,80	0,80	0,80	915±3	14,7±0,7	915±3	14,7±0,7
	1,00	0,80	1,00	915±3	15,3±0,7		
	1,00	0,90	1,00	915±3	16,7±0,7	915±3	16,7±0,7
	1,20	1,10	1,20	915±3	20,0±0,7	915±3	20,0±0,7
235L	1,00	0,90	1,00	957±3	17,3±0,7		
	1,20	1,10	1,20	957±3	20,9±0,8		

* Height in mm - Weight in Kg

** Please check with your local Drumnet contact the availability of all products and related options.

Contact

For any information regarding our products, please contact us:

DRUMNET SA
BP 232
F93523 Saint-Denis Cedex
France

Tel: + 33 1 49.40.78.32
Fax: + 33 1 49.40.78.43
marketing@mausergroup.com
www.drumnet.net



Global support from a local source.